

	Type	L #	Hits	Search Text
1	BRS	L1	68	( measur\$6 detect\$5 sens\$5 transducer determin\$6 )-near3 ( twist-distor\$6 deform\$6 ) - near3 ( rotat\$6 ) near3 ( shaft )
2	BRS	L2	0	1 and ( "pre-program\$6" )
3	BRS	L3	27	1 and (processor computer CPU ECU controller microprocessor microcontroller )
4	BRS	L4	20	3 and ( torque )
5	BRS	L5	4	4 and ( program\$5 )
6	BRS	L6	4	5 and ( time )

	<b>DBs</b>	<b>Time Stamp</b>	<b>Comments</b>	<b>Error Definition</b>	<b>Errors</b>
1	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:31			0
2	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:32			0
3	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:33			0
4	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:33			0
5	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:39			0
6	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/09 11:39			0